introducing the new

pro-struct



.

Our new pro-struct[®] structural screw range is here!

- Specially engineered for UK timber sizes*
- ETA approval pending from German test house, CE marked
- Complies with **RoHS** & **REACH**
- Special steel moves with the wood
- Special thread geometry drives in quicker & gives better pull out resistance
- Large diameter head improves resistance to head pull through
- Zinc plated 500hrs salt spray coating service class 1 & 2 of Eurocode 5
- T+ head marking & screw length on head
- Driver bit in every box

Call our office: +44 (0) 1773 740 410 or contact your representative for more details and samples



Diameter	Length	Drive	Head Diameter	Box Qty	Thread Length	Shank Ribs
			Zinc & Yellov	v		
5mm	40mm	T-25	12mm	200	20mm	х
5mm	50mm	T-25	12mm	200	30mm	х
5mm	60mm	T-25	12mm	200	30mm	х
			Zinc & Clear			
6mm	60mm	T-30	15mm	50	52mm	
6mm	80mm	T-30	15mm	50	52mm	х
6mm	100mm	T-30	15mm	50	52mm	х
6mm	120mm	T-30	15mm	50	52mm	х
6mm	140mm	T-30	15mm	50	75mm	х
8mm	65mm*	T-40	22mm	50	52mm	
8mm	85mm*	T-40	22mm	50	52mm	х
8mm	100mm*	T-40	22mm	50	52mm	х
8mm	115mm*	T-40	22mm	50	52mm	х
8mm	135mm*	T-40	22mm	50	80mm	х
8mm	160mm	T-40	22mm	50	80mm	х
8mm	180mm	T-40	22mm	50	80mm	х
8mm	200mm	T-40	22mm	50	80mm	х
8mm	220mm	T-40	22mm	50	80mm	х
8mm	240mm	T-40	22mm	50	80mm	х
8mm	260mm	T-40	22mm	50	80mm	х
8mm	280mm	T-40	22mm	50	80mm	х
8mm	300mm	T-40	22mm	50	80mm	x

*Diameters M6 – M14 available in lengths up to 1500mm and various head styles to special order.

Available from: Aptus Fastener Systems Ltd, Salterwood Drive, Denby Hall Business Park, Denby, Derbyshire, DE5 8JY, UK Tel: +44 (0) 1773 740 410 Fax: +44 (0) 1773 740 417 Email: sales@aptusfasteners.co.uk Web: www.aptusfasteners.co.uk

